

CL410

SCALE & CORROSION INHIBITOR

Form: Liquid **Color:** Clear Red **Odor:** Mild

- Scale and corrosion protection for ferrous and non-ferrous metals in hot or cold closed systems.
- Contains an Oxygen Scavenger.
- A color indicator signifies an adequate pH level.

CL410 is a scale and corrosion inhibitor for hot water boiler and chilled water recirculating system. **CL410** is a formula designed for use in large and medium closed loop recirculating systems, where control with other formulations is difficult.

CONTROL PARAMETERS:

CL410 treatment dosages should be controlled using a test kit which indicates phosphate (PO₄) levels.

CL410 (PO₄) should be maintained between a reading of 20 - 40 using a comparator.

DIRECTIONS: The dosage of **CL410** will depend on the amount of water contained in the recirculating system. Normal treatment dosage is 1 gallon of **CL410** for every 500 gallons of water contained in the system. **CL410** may be injected directly into the recirculating system through the use of a regular bypass feeder. Mild steel piping and feeding equipment may be used.

In chilled water recirculating systems, a microbiocide is recommended as a preventative treatment or for control if infestation occurs.

SHARE CANADA

1691 Church Avenue, Winnipeg MB R2X 2Y7
Phone: 1-800-665-7692 Fax: 1-800-563-8453