

HI-TEMP RED GREASE

MULTI-SERVICE NON-MELT LUBRICANT

Form: Thick Gel **Color:** Red **Odor:** Typical Petroleum

- Withstands heavy shock load and impact pressures of 65 Timken load capabilities.
- Endures temperatures as high as 1100°F.
- Resists most acids, salts, dirt, salt sprays, steam, corrosion and oxidation.

If the grease you've been using isn't able to withstand the extreme pressure and high temperatures generated by your equipment, it's time to switch to Share's **HI-TEMP RED GREASE**. Not only does **HI-TEMP RED GREASE** endure these tough conditions, but it is also resilient against other harsh contaminants such as most acids, weathering, salt spray, steam, oxidation and dirt. A select combination of adhesives allows **HI-TEMP RED GREASE** to adhere to metal without 'throwing off' or 'slinging out' while your equipment operates at high speeds. Use it on a variety of industrial equipment including blast furnaces, slag pits, ball joints, sleeve bearings, roller bearings, gears, winches, cables, hinges and chains.

Great for use in. . .

Stone Quarries
Hot Strip Mills
Steel Foundries
Cement Plants
Oil Fields
Elevators
Boiler Operations

Paper Mills
Mining Equipment
Sewage Plants
Farm Equipment
Air Conditioners
Wheel Bearings

Timken Retention Test :	8.0 hours
Test Duration:	1.7mm
Scar Width:	0.61 mm
4-Ball Wear, scar diameter (ASTM D-2266)	0.05 gms.
Leakage Tendencies (ASTM D-217)	2.0
NLGI Grade	2.0
Timken OK Load (ASTM D-2509)	65 lbs.
Penetration (ASTM D-2509)	245-265 mm
Water Resistance:	Excellent
Rust Resistance:	Excellent
Acid Resistance:	Excellent
Color:	Red

SHARE CANADA

1691 Church Avenue, Winnipeg, MB R2X 2Y7
Phone: 1-800-665-7692 Fax: 1-800-563-8453