

MARQUISE CUT

WAX STRIPPER CONCENTRATE

Form: Liquid **Color:** Light Yellow **Odor:** Pleasant Floral

- Contains a potent blend of suspending and rinse additives, detergents, ammonium salts, polymer penetrants and co-solvents in a concentrated liquid form.
- Dissolves sealants and finishes within minutes!
- Specifically designed for extracting aqueous finishes, including polymeric, synthetic and natural sealants.

Chip away at old, faded layers of floor finish without spending hours on your hands and knees scrubbing. In only a few minutes the chemical power of **MARQUISE CUT** Floor Finish Stripper will cut away years of wax build-up and eliminate the bond between your floor's natural surface and the previous finish. This heavy duty stripper penetrates deep into the pores of your floor to unlock metal cross-linked finishes and remove stubborn polishes. In fact, **MARQUISE CUT** is so powerful it has the ability to cut through 12 coats of thermoplastic finish with only one application with a mop. While **MARQUISE CUT** will quickly cut through faded finishes, it will not eat away at vinyl or resilient tiles, nor will the low-odor formula overpower you with noxious ammonia fumes.

Other **MARQUISE CUT** Uses . . .

Polymer Cleaner

Use at a 1 to 10 dilution.

Carpet Spot Remover

Apply full strength, test in an inconspicuous spot.

Traffic Lane Cleaner

Use at 1 to 2 dilution.

Gasket Remover

Apply full strength.

Siliconized Coating Remover

Use at a 1 to 5 dilution.

Degreaser

Use at a 1 to 10 dilution.

DIRECTIONS FOR USE: **MARQUISE CUT** has been carefully formulated to remove heavy accumulations of acrylic, natural or synthetic floor finishes without scrubbing.

1. Dust mop entire floor to remove loose dust and dirt.
2. Prepare a stripping solution by diluting 16 to 32 ounces of **MARQUISE CUT** per gallon of **COOL** water. Recommended dilution rates are based upon floors with an accumulation of 10 coats of applied floor finish. To ensure proper solution strength, apply diluted product to a small area of floor. If stripping solution does not cut through all accumulated finish, add more **MARQUISE CUT**.
3. Flood floor with stripping solution with a wet mop.
4. Allow the stripping solution to remain on the floor for 5 to 10 minutes. Do not allow stripping solution to dry on floor.
5. After 5 minutes, 'turn over' stripping solution by agitating with a stripping mop. This action puts fresh solution in contact with accumulated floor finish to complete the stripping process.
6. Pick up the stripping/finish residue with a wet vac or auto scrubber.
7. Damp mop floor with clean, cool water and a clean mop.

SHARE CANADA

1691 Church Avenue, Winnipeg, MB R2X 2Y7

Phone: 1-800-665-7692 Fax: 1-800-563-8453