

RUST CONVERTER

POLYMERIC RUST TRANSFORMER

Form: Liquid **Color:** Beige **Odor:** Bland

- Contains no lead so it can be safely applied by brush, roller, sprayer or dipping.
- Made with a special blend of penetrants and rust transformers suspended in a water-based polymeric solution.
- Safely use in areas where fire or explosive conditions may exist.

When corrosion starts to eat away at your metal surfaces, curb its appetite with **RUST CONVERTER** from Share. You'll never see another product like it. **RUST CONVERTER** literally stops rust and creates a special sealant that protects surfaces from further corrosion. It actually converts ferrous oxide deposits into a black, organic, moisture-resistant material that reinforces and protects the very surface that rust was destroying. **RUST CONVERTER** permanently bonds with metal to resist wind, rain, sun and even salt solutions. It also acts as an excellent primer to prepare metal surfaces for painting. The water-based formula is non-caustic, making it both safe and easy to apply. So if rust is making a meal out of your metal equipment, take a bite out of corrosion with **RUST CONVERTER** from Share.

Use on. . . .

Metal Fences

Aluminum and Metal Roofs

Truck Beds

Snow Plows

Automotive Rust

Buckets of Front End Loaders

Chicken Hatchery Roofs

DIRECTIONS FOR USE: SURFACE APPLICATION: Remove large rust and scale particles with a wire brush or sandpaper. Clean the surface thoroughly to remove dirt, dust and grease. **APPLICATION: SHAKE OR STIR WELL BEFORE USING!** Apply this product using a brush or roller. This product is ready-to-use - NO thinning is required. **COVERAGE:** 500 square feet per gallon on a smooth, non-porous surface. Irregular, porous or textured surfaces may require more product. **DRYING TIME:** The resulting coat will dry to smooth, dark finish in 20 minutes. Apply a second coat to ensure complete transformation of rusty surfaces. Allow 48 hours of cure time before the application of the finished paint coat. For long-lasting protection of iron surfaces, the cured rust converter coating should be sealed with two coats of a high quality oil-based paint. No other primer is required. **CLEAN-UP:** Application equipment should be cleaned immediately with soap and water. **GENERAL:** Do not apply this product if the surface temperatures are below 50°F. Store in a cool, dry place, protected from freezing or temperatures above 100°F. **IMPORTANT: DO NOT RETURN USED MATERIAL TO ORIGINAL CONTAINERS.**

SHARE CANADA

1691 Church Avenue, Winnipeg, MB R2X 2Y7

Phone: 1-800-665-7602 Fax: 1-800-563-8453