



SILICA SOIL BINDER

Soil Binding Agent

- *Stabilizes dust to **increase road life** and reduce repairs.*
- ***Convenient liquid** is easy to transport, apply and clean up.*
- ***Ideal** for dirt race tracks, golf cart paths, lumber yards, campgrounds, surface mining roads, road construction sites, etc.*

With **SILICA SOIL BINDER** from Share, vehicles no longer kick up dust and dirt as they travel down unpaved roads. When properly applied, it binds road sand and soil together so that it remains on the ground. **SILICA SOIL BINDER** causes road dust to compress together forming a hard surface that makes travel easier for any vehicle and increases the load bearing capacity of unpaved roads.

Other Uses:

Dirt Race Tracks, Golf Cart Paths, Lumber Yards, Campgrounds, Surface Mining Roads, Road Construction Sites

Directions:

For stabilization and dust control on existing smooth roads, dilute 1 to 6 gallons of **SILICA SOIL BINDER** in 1000 gallons of water. Apply diluted solution at a rate of 20 gallons per 1000 square feet. Repeat this application for 3 consecutive days. Soils with a high sand content will require a heavier treatment. For stabilizing worn roads, blade the road smooth to sub-base and apply the above solution at the rate of 20 gallons per 1000 square feet. Wet the bladed material with solution, spread back over the road and smooth with a roller. Repeat this application for 5 consecutive days.