



# ANTI-SEIZE 2013

## High Temperature & Pressure Lubricant

- **Resists** moisture, weather, steam, chemical fumes and salt spray.
- Seals to plate, to **protect and prevent metal surfaces from seizing and galling** at temperatures up to 2,100°F.
- No mess, **clinging formula** is designed for use on pipe and hose connections, gaskets and all other types of threaded fasteners.

This copper-based lubricant contains a group of incredible ingredients that prevent parts from seizing and galling when operating under intense heat and pressure. **ANTI-SEIZE** has been tested to endure temperatures as high as 2,100°F. Liberally spray this aerosol lubricant onto all moving parts. When sprayed onto threaded components, **ANTI-SEIZE** ensures a tight lubricating film between parts while simultaneously preventing corrosion and seizing.

### Other Uses:

---

Pipe Threads, Motors, Turbines, Engines, Bearings, Gears, Gaskets, Boilers, Oil & Ore Drills, Exhaust Systems, Heat Exchangers, Torque Tools,

### Directions:

---

Surface must be free of dirt, grease and oil. Shake can until agitator ball begins to rattle freely for at least 30 seconds. In upright position, hold nozzle 8 to 10 inches from surface and apply by spraying **ANTI-SEIZE** in short bursts. After using, clean the spray nozzle by turning can upside down and spraying until only gas is expelled.