

- Contains alkaline cleaners making it a powerful detergent.
- Safe to use on most painted surfaces.
- Cuts through tough fats, waxes, greases and grimy soils.

Difficult grease problems call for powerful solutions. For a powerful cleaner that fights tough grime and filth, use Share's **FORMULA 10 DEGREASER NI**. A number of wetting agents, detergents and emulsifiers provide the necessary power you need to cut through thick layers of filth. **FORMULA 10 DEGREASER NI** is a versatile, all-purpose detergent that safely cleans just about any hard, non-porous surface. Because it's also a soluble, concentrated cleaner, **FORMULA 10 DEGREASER NI** is ideal for cutting through tough grime deposits even when diluted. When you need a cleaner to effectively fight grease and other soils, get **FORMULA 10 DEGREASER NI** is **NI** from Share.

## **Other Uses:**

(dilution)

Fire Hose Cleaner (1:20), Buffer Pad Cleaner (1:4), Coil Cleaner (1:10), Hot Tank Degreaser (1:10), Wire Rim Cleaner (1:10), RV Cleaner (1:30), Laundry Pre-soak (1:15), Butyl Wax Stripper (full strength)

## **Directions:**

Recommended dilutions range from 1 part **FORMULA 10 DEGREASER NI** to 5 parts of water for stubborn cleaning problems to 1:15 for light duty use. Extremely difficult cleaning problems may require a stronger solution or second application.

AS A FOAM TANK CLEANER: For large volume sprayers, 1 quart will treat up to 100 gallons of solution. Be certain to circulate **FORMULA 10 NI** (CHEM TITAN) throughout the entire spray system for at least 5 to 10 minutes. Use a high pressure spray or hose to rinse all interior areas and spray tank walls. Drain hoses, spray lines and nozzles, then rinse tank and spray areas thoroughly. For hand held sprayers, use 3 ounces of **FORMULA 10 NI** (CHEM TITAN) per 1 gallon of water, agitate thoroughly and drain. Rinse thoroughly with a clean water rinse.

To USE AS A COIL CLEANER: Dilute **FORMULA 10 NI** (COIL CLEANER) at the rate of 1:5 to 1:15. Spray diluted solution on areas to be cleaned and allow to act on deposits for 10 to 15 minutes. Flush thoroughly with clean water to remove loosened soil and grease. Heavy deposits may require a second treatment.

