

# ANTI-SEIZE 2013

## HIGH TEMPERATURE & PRESSURE LUBRICANT

**Form:** Liquid    **Color:** Grey    **Odor:** Solvent

- Resists moisture, weather, steam, chemical fumes and salt spray.
- Seals to plate, to protect and prevent metal surfaces from seizing and galling at temperatures up to 2,100°F.
- No mess, clinging formula is designed for use on pipe and hose connections, gaskets and all other types of threaded fasteners.

This copper-based lubricant contains a group of incredible ingredients that prevent parts from seizing and galling when operating under intense heat and pressure. **ANTI-SEIZE** has been tested to endure temperatures as high as 2,100°F. Liberally spray this aerosol lubricant onto all moving parts. When sprayed onto threaded components, **ANTI-SEIZE** ensures a tight lubricating film between parts while simultaneously preventing corrosion and seizing.

**ANTI-SEIZE** uses. . .

Pipe threads	Gaskets
Motors	Boilers
Turbines	Oil & Ore Drills
Engines	Exhaust systems
Bearings	Heat exchangers
Gears	Torque tools

**DIRECTIONS:** Surface must be free of dirt, grease and oil. Shake can until agitator ball begins to rattle freely for at least 30 seconds. In upright position, hold nozzle 8 to 10 inches from surface and apply by spraying **ANTI-SEIZE** in short bursts. After using, clean the spray nozzle by turning can upside down and spraying until only gas is expelled.

SHARE CANADA  
1691 Church Avenue, Winnipeg, MB R2X 2Y7  
Phone: 1 800 665 7692 Fax: 1 800 563 8453